

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
16 June 2005 (16.06.2005)

PCT

(10) International Publication Number
WO 2005/053772 A1

(51) International Patent Classification⁷: **A61M 1/36**

(21) International Application Number:
PCT/EP2004/012372

(22) International Filing Date:
2 November 2004 (02.11.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
03026855.1 24 November 2003 (24.11.2003) EP
03026854.4 24 November 2003 (24.11.2003) EP

(71) Applicant (for all designated States except US): **GAMBRO LUNDIA AB** [SE/SE]; Magistratsvägen 16, S-22643 Lund (SE).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **DANNENMAIER, Jürgen** [DE/DE]; Grünenwaldstrasse 88, D-72336 Balingen (DE). **GOEHL, Hermann** [DE/DE]; Rosengarten 2, D-72406 Bisingen (DE). **ERTL, Thomas**

[DE/DE]; Marienburgstrasse 56, D-72406 Bisingen (DE). **CHEVALLET, Jacques** [FR/FR]; 8 route de Ternay, F-69360 Serezin du Rhône (FR). **RIBOLZI, Francesco** [IT/IT]; via Camatta 1, I-41100 Modena (IT).


(74) Agent: **LEJEUNE, Daniel**; Gambro Patent Department, 61 avenue Tony Garnier, F-69007 Lyon (FR).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LU, MC, NL, PL, PT, RO, SE,

[Continued on next page]

(54) Title: DEGASSING DEVICE AND END-CAP ASSEMBLY FOR A FILTER INCLUDING SUCH A DEGASSING DEVICE



(57) Abstract: A degassing device (203) comprises a first chamber (21) having an inlet for a liquid, and a second chamber (22) having an opening (23) closed by a hydrophobic membrane (24) and an outlet (25) for discharging the liquid. The first chamber (21) has a downstream portion that partially extends within the second chamber (22) and communicates therewith by a passageway (28). The second chamber (22) has a downstream portion that extends below the passageway (28) and asymmetrically surrounds the downstream portion of the first chamber (21).

WO 2005/053772 A1



SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:

- *as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ,*

BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

Published:

- *with international search report*
— *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

DEGASSING DEVICE AND END-CAP ASSEMBLY FOR A FILTER INCLUDING SUCH A DEGASSING DEVICE

The present invention relates to a degassing device and an end-cap assembly for a filter including such a degassing device.

A conventional filter for extracorporeal treatment of blood comprises a first and a second compartments separated by a membrane, the first compartment having an inlet and an outlet for the circulation of blood therethrough and the second compartment having an outlet for draining a liquid (e.g. plasma water, plasma, used dialysis liquid) and an inlet when the treatment (e.g. hemodialysis) requires the circulation of a treatment liquid (e.g. a dialysis liquid) in the second compartment. The membrane is enclosed in an elongated tubular housing closed at both ends by an end-cap comprising a nozzle used as an inlet/outlet port for the first compartment.

Such filters are used in various extracorporeal treatments of blood, such as hemodialysis, hemofiltration, hemodiafiltration, plasmapheresis. The same type of filter, usually referred to as hemodialyzer or hemofilter, is used for hemodialysis, hemofiltration, hemodiafiltration. The main difference between a hemodialyzer and a plasmafilter (i.e. a filter used in plasmapheresis) is the pore size of their respective membrane, a membrane for plasmapheresis allowing the proteins contained in blood to migrate therethrough, whereas a membrane for hemodialysis does not.

In all these treatments, blood is withdrawn from the patient, flown through the first compartment of the filter, and returned to the patient. In hemodialysis, a dialysis liquid is simultaneously flown through the second compartment of the filter and the metabolic wastes (urea, creatinine) contained in blood migrate by diffusion through the membrane into the second compartment. In hemofiltration, a pressure difference is created across the membrane so that plasma water flows through the membrane into the second compartment of the filter. Here, metabolic wastes migrate by convection into the second compartment. In order to compensate for the loss of bodily fluid, the patient is simultaneously infused a sterile substitution

solution. Hemodiafiltration is a combination of hemodialysis and hemofiltration, and, in this treatment, a dialysis liquid is flown through the second compartment and a substitution liquid is infused into the patient. In plasmapheresis, a pressure difference is created across the membrane so that plasma (i.e. plasma water and proteins) flows through the membrane into the second compartment of the filter. Once treated, the plasma is returned to the patient.

A machine for performing any of the above treatments comprises a peristaltic pump for withdrawing blood from a patient through a so-called "arterial" line connected at one end to the vascular circuit of the patient and at the other end to the inlet of the first compartment of a filter, for pumping blood into the filter, and for returning blood to the patient through a so-called "venous" line connected at one end to the outlet of the first compartment of the filter and at the other end to the vascular circuit of the patient. The treatment machine also usually comprises a first blood pressure sensor for measuring the pressure of blood in the arterial line upstream of the pump, a second blood pressure sensor for measuring the pressure of blood in the arterial line downstream of the pump, a third pressure sensor for measuring the pressure of blood in the venous line, a bubble detector for detecting air bubbles in the venous line and a clamp for closing the venous line, for example when air bubbles are detected by the bubble detector.

An arterial line typically comprises the following components connected together by segments of flexible tubes: a first Luer connector for connection to an arterial cannula, an arterial bubble trap, a pump hose for cooperating with the rotor of the peristaltic pump of the treatment machine, and a second Luer connector for connection to the inlet of the first compartment of the filter.

A venous line typically comprises the following components connected together by segments of flexible tubes: a first Luer connector for connection to the outlet of the first compartment of the filter, a venous bubble trap, and a second Luer connector for connection to a venous cannula. Usually, the first and third pressure sensors of the machine are connected to the arterial and venous bubble trap respectively, when the treatment machine, the arterial line, the venous line and the filter are assembled in view of a treatment.

A conventional bubble trap is basically an elongated container that, in use, is held vertically. The container has an inlet and an outlet for blood that are arranged so as not to be adjacent. It comprises also, in an upper location, a pressure measuring port for connection to a pressure sensor, an infusion port for infusing a liquid (e.g. a drug or a sterile saline solution) and an injection port for adding or removing air into or from the bubble trap so as to adjust the level of blood therein. In use, the bubble trap contains a volume of blood in a lower part that transiently stagnates therein so as to let gas bubbles and micro bubbles escape by gravity and join an upper part of the container full of air. In a conventional bubble trap, there is therefore always an interface blood-air.

Besides the fact that, in order to properly operate, conventional bubble traps must contain a certain volume of blood (which conflicts with the desirable minimization of the volume of blood outside of the body during extracorporeal blood treatments), their use is limited to relatively short treatment sessions because of the blood clotting resulting from long lasting blood-air interface. In this respect, they are adapted to chronic treatment (a treatment session for a chronic patient usually lasts about four hours), but they cannot be used for intensive care treatment (the treatment of an acute patient can last several days).

In addition, the assemblage of a bubble trap and the line connected thereto to a treatment machine and the setting of the blood level therein is relatively time consuming.

An object of the invention is to design a degassing device and an end-cap assembly including such a degassing device that remedy the above-mentioned limits of conventional extracorporeal blood circuit.

According to the invention, a degassing device comprises:

- a first chamber having an inlet for a liquid; and
- a second chamber having an opening closed by a hydrophobic membrane and an outlet for discharging the liquid,

wherein the first chamber has a downstream portion that partially extends within the second chamber and communicates therewith by a passageway, and the second chamber has a downstream portion that extends below the passageway and asymmetrically surrounds the downstream portion of the first chamber.

5

This degassing device presents several advantages.

First, it is very efficient and remains efficient over time. Also it allows for a compact design, i.e. a small internal volume. For example, It is possible to design such a degassing device with a total internal volume that is about half of the blood volume in conventional bubble traps.

10

Second, the degassing device operates without air-blood interface and it is therefore particularly adapted to long lasting treatments (e.g. continuous renal replacement therapies).

Third, it does not require any specific activity for its mounting on a treatment machine or for its setting in use (no adjustment of the level of the air-blood interface since there is no air-blood interface).

15

Additional or alternative features of the degassing device according to the invention are as follows:

- The downstream portion of the second chamber has a lateral wall that surrounds a longitudinal axis of the degassing device and a bottom wall that is inclined with respect to a longitudinal axis of the degassing device.

20

- The downstream portion of the first chamber has a lateral wall that is concentric to the lateral wall of the second chamber.

25

- The lateral wall of the downstream portion of the first chamber and the lateral wall of the downstream portion of the second chamber are substantially cylindrical.

- The downstream portion of the first chamber has a cross-section that is substantially the same as the cross-section of the passageway between the first and the second chamber.

30

- The downstream portion of the first chamber is substantially conical and the passageway between the first and the second chamber opens at the tip of the cone.

5 - The passageway between the first and the second chamber opens in the second chamber close to a wall delimiting an upstream portion of the second chamber.

- The first chamber comprises an upstream portion having a decreasing cross section.

10

- The first chamber comprises an upstream portion having an increasing cross section.

15

- The second chamber comprises an upstream portion extending above the passageway that has a decreasing cross-section, with a larger cross-section that is substantially level with the passageway and a smaller cross-section that is substantially level with the hydrophobic membrane.

- The upstream portion of the second chamber is substantially frusto-conical.

20

- The outlet port opens in the downstream portion of the second chamber at a location furthest to the passageway.

25

- The ratio of the diameter of the passageway to the diameter of the second chamber at the level of the passageway is comprised between about 0,2 and about 0,5.

30

- The first chamber of the degassing device has a downstream portion having a cross-section selected with respect to a maximal flow rate of a liquid in a circuit connected to the degassing device so that the velocity of the liquid in the downstream portion of the first chamber is less than a predetermined velocity.

- The cross-section of the downstream portion of the first chamber is selected with respect to a maximal flow rate of a liquid of about 500ml/min in a circuit connected

to the degassing device so that the velocity of the liquid in the downstream portion of the first chamber is less than about 3m/min.

- 5 - The cross-section of the second chamber of the degassing device at the level of the passageway is selected so that the ratio of the velocity of a liquid within a downstream portion of the first chamber to the velocity of the liquid within the second chamber at the level of the passageway is more than a determined value.
- 10 - The cross-section of the second chamber of the degassing device at the level of the passageway is selected so that the ratio of the velocity of the liquid within the downstream portion of the first chamber to the velocity of the liquid within the second chamber at the level of the passageway is at least about 2.
- 15 - The downstream portion of the second chamber forms an overflow for a fluid flowing from the first chamber into the second chamber.
- 20 - The first chamber, the second chamber and the passageway therebetween are arranged with respect to each other so that a flow pattern of a liquid flowing from the first chamber, through the second chamber and to the outlet port comprises a component that is tangential to the membrane.
- 25 - The flow pattern of a liquid flowing from the first chamber, through the second chamber and to the outlet port comprises an umbrella like component.
- 30 - The first chamber, the second chamber and the passageway therebetween are arranged with respect to each other so that a flow of liquid flowing from the first chamber, through the second chamber and to the outlet port keeps gas bubbles in motion along an inner surface of the hydrophobic membrane.
- The degassing device further comprises an inlet port for the infusion of liquid.
- The degassing device further comprises a pressure measurement port for connection to a pressure sensor.

7

- The degassing device further comprises a protective member for protecting the hydrophobic membrane against external blows and for limiting the deformation of the hydrophobic membrane when the pressure of the liquid within the degassing device exceeds a limit.

5

- The hydrophobic membrane is arranged in a plane substantially perpendicular to a longitudinal axis of the degassing device.

According to the invention, an end-cap assembly for a filtration device including a
10 filtration membrane arranged in an elongated housing comprises:

- an end-cap having:
 - an end wall having a central axis,
 - a peripheral wall surrounding the end wall, for connection to an end of the housing, and
- 15 • a degassing device as defined above, connected to the end-cap so that the first chamber of the degassing chamber is in fluid communication with an interior of the en-cap.

Additional or alternative features of the end-cap assembly according to the
20 invention are as follows:

- The degassing device has a longitudinal axis that coincides with the central axis of the end wall of the end-cap and the first chamber has a wall directly connected to the end wall of the end-cap.

25

- The end wall of the end-cap is substantially annular and the wall of the first chamber has circular cross section decreasing from a first end of larger section, by which the first chamber is connected to the end wall of the end cap, to a second end of smaller cross section forming the passageway between the first chamber
30 and the second chamber.

- The degassing device has a longitudinal axis that is substantially parallel to and spaced apart from the central axis of the end wall of the end-cap, and the end cap

8

assembly further comprises a lateral nozzle for connecting an interior of the end-cap to an inlet of the first chamber of the degassing device.

- 5 - The first chamber has a wall having circular cross section increasing from a first end of smaller section, which forms the inlet of the first chamber, to a second end of larger cross section, which forms the passageway between the first and the second chamber.

10 Another object of the invention is a filter including the end-cap assembly defined above.

Other features and advantages of the invention will appear on reading the detailed description that follows. Reference will be made to the appended drawings in which:

15

Figure 1 is a cross-section view of a filter according to the invention, along a plane that contains the longitudinal axis of the filter;

20 Figure 2 is a perspective view of a first embodiment of an end-cap assembly according to the invention;

Figure 3 is a cross-section view of the end-cap assembly of Figure 2, along a plane that contains the central axis of the end-cap;

25 Figure 4 is a front view of a second embodiment of an end-cap assembly according to the invention;

Figure 5 is a cross-section view of the end-cap assembly of Figure 4, along a plane that contains the central axis of the end-cap;

30

Figure 6 is a perspective view, partially cut-away, of a third embodiment of the end-cap assembly according to the invention;

Figure 7 is a cross-section view of the end-cap assembly of Figure 6, along a plane that contains the central axis of the end-cap;

Figure 8 is a cross-section view of a degassing device according to the invention,
5 along a plane that contains the central axis of the end-cap;

Figure 9 is a front view of the degassing device of Figure 8;

Figure 10 is cross-section view of a fourth embodiment of the end-cap assembly
10 according to the invention, along a plane that contains the central axis of the end-cap; and

Figure 11 is cross-section view of a fifth embodiment of the end-cap assembly
15 according to the invention, along a plane that contains the central axis of the end-cap.

Figure 1 shows a hollow fiber filter 1 comprising a tubular housing 2 having a longitudinal axis 3, a semi-permeable membrane in the form a bundle of hollow fibers 4 extending within the housing 2 and secured thereto at both ends, and two
20 end-caps 5, 6 closing the housing 2 at both ends. The ends of the fibers 4 are secured to the housing 2 by a potting compound in which they are embedded. The potting compound forms a disk 7 that extends perpendicularly to the longitudinal axis 3 of the housing 2. The ends of the fibers 4 open on an outer surface 8 of the disks 7 of potting material.

25

By construction, the hollow fiber filter 1 comprises a first and a second compartments separated from each other. The first compartment includes the interior of the hollow fibers 4 and the space delimited at each end of the filter between the outer surface 8 of the disk 7 of potting compound and the inner
30 surface of the end-cap 5, 6, and the second compartment includes the space outside of the hollow fibers 4 that is delimited by the inner surface of the housing 2 and the inner surface 9 of the disks 7 of potting material. The housing 2 is fitted with two nozzles 10, 11 that give access to the second compartment.

In operation, the filter 1 is held substantially vertical, with the end-cap 6 in the lower position and the end cap 5 in the upper position.

5 The lower end-cap 6 comprises a circular end-wall 12 connected to a tubular peripheral wall 13 by which the end-cap 6 is secured to the housing 2. When the end-cap 6 is secured to the housing 2, as shown, the end-wall 12 is substantially perpendicular to the longitudinal axis 3 of the filter 1 and the tubular peripheral wall 13 is concentric to the housing 2. The end-cap 6 also comprises a tubular nozzle 14 connected to the end-wall 12 so that the central axis of the nozzle 14 coincides
10 with the longitudinal axis 3 of the housing 2. The nozzle 14 forms the inlet of the first compartment.

The upper end-cap 5 comprises an annular end-wall 15 connected to a tubular peripheral wall 16 by which the end-cap 5 is secured to the housing 2. When the
15 end-cap 5 is secured to the housing 2 of the filter 1, as shown, the longitudinal axis 3 of the filter 1 coincides with a central axis of the end wall 15, and the tubular peripheral wall 16 is concentric to the housing 2 of the filter 1.

According to the invention, the end-cap 5 is connected to a degassing device 201
20 so as to form the end-cap assembly that is shown in details in Figures 2 and 3. The degassing device 201 has a longitudinal axis 27 that coincides with the longitudinal axis 3 of the filter 1, when the end-cap is secured to the housing 2 of the filter 1. The degassing device 201 comprises a first chamber 21 for receiving a liquid flowing out of the first compartment of the filter 1 into the end-cap 5; a
25 second chamber 22 in communication with the first chamber 21 and having an opening 23 closed by a hydrophobic membrane 24; and an outlet port 25 connected to the second chamber 22 for discharging the liquid.

The first chamber 21 is delimited by a funnel like wall 26 having a first end of larger
30 cross section, by which it is connected to the end-wall 15 of the end-cap 5, and a second end of smaller cross section, which defines a passageway 28 between the first chamber 21 and the second chamber 22. The funnel like wall 26 is centered on the longitudinal axis 27 of degassing device 201. In the direction of the flow, the first chamber 21 has therefore an upstream portion having a decreasing cross-

section and a downstream portion having a constant cross-section (unless otherwise specified, "cross-section" means here and hereunder the transversal cross-section with respect to the longitudinal axis 27; also, the "direction of flow" means the direction of flow from the first compartment of the filter 2 to the outlet
5 port 25 through the first and the second chambers 21, 22 of the degassing device 201).

The second chamber 22 has an upstream portion and a downstream portion that extend on each side of a plane containing the passageway 28 between the first
10 and the second chambers 21, 22. The downstream portion is delimited by a cylindrical wall 29 that is concentric to the tubular portion of the funnel like wall 26, and by a bottom wall 30 that is beveled of about 45 degrees with respect the longitudinal axis 27. The highest point of the oblique bottom wall 30 is adjacent to the rim of the cylindrical wall 29. It results from the respective arrangement of the
15 first chamber 21 and of the downstream portion of the second chamber 22 that the second chamber 22 forms an overflow for a liquid flowing from the first chamber 21 into the second chamber 22.

The outlet port 25 is comprised of a tubular wall that is connected to the cylindrical
20 wall 29 of the second chamber 22, at the lowest point thereof. The central axis of the outlet port 25 is substantially perpendicular to the longitudinal axis 27 of the degassing device 201. The outlet port 25 extends tangentially to the cylindrical wall 29 of the second chamber 22.

25 It results from the shape of the second chamber 22 (cylindrical wall 29 connected to a slanting bottom wall 30), and from the connection of the outlet port 25 at the lowest point thereof, two characteristics that are of particular interest for a degassing device intended for blood: in comparison to a second chamber that would completely and symmetrically surround the first chamber or even only the
30 upstream cylindrical portion of the first chamber, with a bottom wall substantially perpendicular to the longitudinal axis of the degassing device, the design represented in the figures allows for a degassing device having a minimal internal volume, and in which there is no area of relative stagnation for a liquid circulated through the degassing device. It was observed during the research work that led to

the present invention, that with a second chamber completely surrounding the first chamber, with a bottom wall substantially perpendicular to the longitudinal axis of the degassing device, an area of relative stagnation appears in the second chamber opposite to the outlet port.

5

The upstream portion of the second chamber 22 is delimited by a lid 31 having a lower rim that is so dimensioned as to snugly engage an outer annular rabbet of the upper rim of the cylindrical wall 29. The lid 31 comprises a first, frusto-conical, wall 32 connected to a second, cylindrical, wall 33, the first wall 32 being
10 connected to the second wall 33 by its smaller section. Note that the first wall 32 comprises in fact two frusto-conical portions, the lower portion having an angle that is slightly larger than the angle of the upper portion. The upstream portion of the second chamber 22 has therefore a decreasing cross-section. The lid 31 further comprises an inner annular shoulder 34 that extends at the junction
15 between the frusto-conical wall 32 and the cylindrical wall 33. The aperture defined by the inner annular shoulder 34 forms the opening 23 of the second chamber 22 mentioned above. The annular shoulder 34 supports the hydrophobic membrane 24 at the periphery thereof. The membrane 24 is secured to the lid 31 by an O-ring 35 resting at the periphery of the membrane 24 and against which a disk-shaped
20 stopper 36 is tightly engaged. The stopper 36, which snugly fits within the cylindrical wall 33 of the lid 31, comprises a vent 37 in its center through which the air removed from the liquid in the degassing device 30 can escape. Note that the membrane 24 does not abut on the inner surface of the stopper 36. The membrane 24 can therefore deform to a certain extent. When the positive
25 pressure in the filter exceeds however a determined value, the membrane 24 abuts on the stopper 36 and does not run the risk of rupturing.

Three ports 38, 39, 40 are connected to the first chamber 21. The inlet ports 38, 39, 40 can be used for the infusion of various liquid (e.g. a substitution liquid or a
30 drug, when the filter is a hemofilter) and for connection to a pressure sensor.

It results from the respective arrangement of the first chamber 21 and of the of the second chamber 22 that a liquid circulated through the degassing device 201 has an umbrella pattern with a longitudinal component within the first chamber 21 and

a radial component within the upstream portion of the second chamber 22. The radial component of the flow tangentially sweeps the hydrophobic membrane 24 and helps prevent the formation of blood foam along its internal surface while keeping bubbles and micro bubbles in constant motion along the membrane until
5 they escape therethrough.

Its is possible to optimize the efficiency of the degassing device of the invention by selecting the diameter of the downstream cylindrical part of the first chamber 21 (upper part of the wall 26) with respect to the maximal flow rate of blood within the
10 extracorporeal blood circuit, as well as the size of the second chamber 22 (diameter of the cylindrical wall 29) with respect to the size of the first chamber 21 (diameter of the upper part of the wall 26) so that:

- the maximal velocity of the liquid in the first chamber 21 (corresponding the maximal flow rate in the extracorporeal blood circuit) is never high enough to
15 prevent the bubbles and micro-bubbles from migrating towards the hydrophobic membrane 24 and to expel them to the outlet port 25;
- the velocity of the liquid entering the second chamber decreases to such an extent that bubbles and micro-bubbles can migrate by gravity towards the hydrophobic membrane 24.

20

For example, for a maximal blood flow rate of about 500ml/min within the extracorporeal blood circuit, it was determined during the researches that led to the invention that an optimal velocity of blood within the downstream portion of the first chamber 21 (cylindrical part of wall 26) should be less than about 3 m/min and
25 that the optimal ratio of the velocity of blood within the downstream portion of the first chamber 21 to the velocity of blood within the second chamber 22 at the level of the passageway 28 should be at least about 2.

A prototype of the degassing device 201 was made of molded polycarbonate: the
30 diameter of the downstream portion of the first chamber 21 (cylindrical part of wall 26) was 16 mm; the inner diameter of the second chamber 22 at the level of the passageway 28 was 19 mm; the outer diameter of the second chamber 22 at the level of the passageway 28 was 32 mm; the diameter of the hydrophobic membrane 24 (useful surface) was 27 mm; the distance between the passageway

28 and the hydrophobic membrane 24 was 5 mm. The membrane was made of polytetrafluoroethylene and had a thickness of 0,13 mm and a pore size of 0.2 μm .

Bovine blood was circulated at a flow rate of 500ml/mn in a closed loop circuit including a hemofilter connected to the prototype of degassing device 201. The velocity of blood within the degassing device was:

- 2,5 m/min in the downstream cylindrical portion of the first chamber 21;
- 2 m/min between the passageway 28 and the hydrophobic membrane 24;
- 1 m/min in the downstream portion of the second chamber 22, just below the level of the passageway 28; and
- 2 m/min in the downstream portion of the second chamber 14, just upstream of the outlet port 25.

The pressure in the degassing device was 50 mmHg. After four hours, 5 ml of air was injected in the circuit upstream of the hemofilter. After 15 minutes, the air injected in the circuit had been totally removed by the degassing device 201.

The end-cap 5, the walls 26, 29 and 30 that delimit the first chamber 21 and the downstream portion of the second chamber 22, and the ports 25 38, 39, 40 connected thereto, can be made by molding in one piece from a plastic material. A biologically inert material like polycarbonate is appropriate when the filter is for medical use. The lid 31 can also be made in one piece by molding, from the same material as the end-cap 5 and walls 26, 29, 30. The hydrophobic membrane 24 can be made of polytetrafluoroethylene.

The degassing device 201 is particularly adapted to remove gas from blood in an extracorporeal circuit of blood. The operation of the degassing device 201 in connection with, for example, the hemofilter 1, is as follows. Before a treatment session, the inlet of the first compartment (nozzle 14 of end-cap 6) of the hemofilter 1 is connected to an arterial blood line, and the outlet port 25 of the blood degassing device 201 is connected to a venous blood line. The hemofilter 1 is engaged in a holder keeping it substantially vertical, with the degassing device 201 being in the upper position. A bag of sterile saline solution is connected to the arterial line and the solution is pumped into the arterial line, the first compartment

of the hemofilter 1, the degassing device 201 and the venous line, so as to rinse the extracorporeal blood circuit, to fill it with sterile saline solution and to remove air therefrom (preparatory steps called "priming" of the extracorporeal blood circuit). At the end of this process, there is no more air in the degassing device
5 201. Then, the arterial line is connected to a blood vessel of a patient, blood is pumped into the extracorporeal circuit while the saline solution flowing out of the venous line is collected in a waste bag. When blood reaches the end of the venous line, the venous line is in turn connected to the vessel of the patient and the treatment proper can start.

10

In the hemofilter 1, the blood flows within the hollow fibers 4, enters the end-cap 5, flows through the first chamber 21, pours into the second chamber 22 and leaves the degassing device 201 via the outlet port 25. Since the cross-section of the second chamber 22 at the level of the passageway 28 is substantially larger than
15 the cross-section of the passageway 28 itself, the blood flow substantially decreases when blood enters the second chamber 22. This helps the bubbles and micro-bubbles that may be present in blood to move upwards by gravity towards the hydrophobic membrane 24. Also, because blood is directed by the funnel like wall 26 towards the hydrophobic membrane 24 and from then towards the frusto-
20 conical wall 32 of the lid 31, the overall flow pattern of blood is umbrella like with a component that is tangential to the hydrophobic membrane 24. The membrane is therefore permanently swept and the creation of a layer of static blood foam on the inner surface of the membrane 24 is prevented. Instead, in particular thanks to the frusto-conical shape of the wall 32, the bubbles and micro-bubbles are kept in a
25 permanent motion at the vicinity of the membrane 24, through which they pass shortly after entering the second chamber 22.

30

Figures 4 and 5 show a second embodiment of a degassing device 202 connected to an end-cap 5 according to the invention. The main differences between this second embodiment and the first embodiment of figures 1 to 3 are as follows:

- The outlet port 25 of the degassing device 202 is comprised of a tubular wall that is connected to the inclined wall 30 of the second chamber 22, at a lower point thereof. The central axis of the outlet port 25 is substantially perpendicular to the

longitudinal axis 27 of the degassing device 202. The outlet port 25 extends inwardly, that is below the inclined wall 30 of the second chamber 22, tangentially to the upper cylindrical portion of the wall 26 of the first chamber 21.

5 - The degassing device 202 is not fitted with any additional port (for the infusion of various liquid or for connection to a pressure sensor).

- The upstream portion of the second chamber 22 is defined within a capsule like lid 31 fitting on the upper rim of the cylindrical wall 29 of the second chamber 22.

10 More specifically, the upstream portion of the second chamber 22 is delimited by an inner peripheral wall 43 of the lid 31, which has a slightly frusto-conical inner surface, and by a circular hydrophobic membrane 24 closing an opening 23 of the second chamber 22 within the lid 31 defined by an inner annular shoulder 34. The hydrophobic membrane 24 is secured (e.g. by gluing) at its periphery to the
15 shoulder 34 and is perpendicular to the longitudinal axis 27 of the degassing device. In more details, the capsule like lid 31 comprises a circular flat top wall 44 connected to the inner peripheral wall 43 and to an outer peripheral wall 42. The inner peripheral wall 43 and the outer peripheral wall 42 define therebetween a
20 groove corresponding to the upper rim of the cylindrical wall 29 of the second chamber 22, so that the lid 31 can be engaged into the rim of the cylindrical wall 29 and secured thereto, e.g. by gluing. The lid 31 also comprises a vent 37 in the middle of the circular flat top wall 44. The annular shoulder 34 is spaced apart from the top wall 44 of the lid 31 so that the hydrophobic membrane 24 can deform under positive pressure. The top wall 44 of the lid 31 essentially protects the
25 hydrophobic membrane 24 against outside blows.

Figures 6 and 7 show a third embodiment of the invention. The main difference between this third embodiment and the first embodiment of figures 1 to 3 resides in the connection of the degassing device 203 to the end cap 50. In the
30 embodiment of figures 1 to 3, the degassing device 201 is connected on the top of the end-cap 5 so that the longitudinal axis 27 of the degassing device 201 coincides with the central axis of the end cap 5. In the embodiments of figures 6 and 7, the degassing device 203 is laterally connected to the end-cap 50 so that

the longitudinal axis 27 of the degassing device 203 is parallel to and offset with respect to the central axis 3 of the end cap 50.

5 In more details, the end-cap 50 comprises a circular end-wall 51 connected to a tubular peripheral wall 52 by which the end-cap 50 is secured to the housing 2 of a filter. The end-cap 50 further comprises a nozzle 53 that radially extends from the circular end wall 51 so that the longitudinal axis of the nozzle 53 is perpendicular to the central axis of the end-cap 5. The nozzle 53 is fitted with a female Luer connector.

10

The degassing device 203 is very similar to the degassing device 201 shown in Figures 1 to 3, save for two characteristics:

15 - The central axis of the outlet port 25 intersects and is substantially perpendicular to the longitudinal axis 27 of the degassing device 203.

20 - The first chamber 21 comprises a conical upstream portion connected by its larger section to the downstream cylindrical portion. The inlet 54 of the first chamber 21 opens at the tip of the conical upstream portion. Also, the degassing device 203 comprises a coupling base 55 fitted with a male Luer connector 56 complementary to the female Luer connector of the nozzle 53 of the end-cap 50. The connecting base 55 includes a channel 57 that connects the inlet 54 of the first chamber 21 to the bore of the male Luer connector 56. The longitudinal axis of the channel 57 and of the bore of male Luer connector 56 coincide and are
25 perpendicular to the longitudinal axis 27 of the degassing device 203.

Figures 8 and 9 show another embodiment of degassing device according to the invention. The main differences between this degassing device and the degassing device of figures 4 and 5 are as follows:

30

- The wall of the upstream portion of the first chamber 21 of the degassing device 204 is frusto-conical and connects by its larger section to the downstream cylindrical wall 26.

- The outlet port 25 of the degassing device 204 is comprised of a tubular wall that is connected to the inclined wall 30 of the second chamber 22, at a lower point thereof. The central axis of the outlet port 25 is substantially parallel to the longitudinal axis 27 of the degassing device 205. The outlet port 25 extends
5 downwardly, that is below the inclined wall 30 of the second chamber 22, tangentially to the upper cylindrical portion of the wall 26 of the first chamber 21.

- The lower rim of the frusto-conical wall 58 of the lid 31 comprises an annular inner rabbet. The upper rim of the cylindrical wall 29 of the second chamber 22
10 comprises a corresponding outer annular rabbet so that the lid 31 can engage the cylindrical wall 29 and form therewith a tight joint. The rims of the lid 31 and of the cylindrical wall 29 are dimensioned so that when the lid 31 is engaged on the top of the circular wall 29 the inner surfaces thereof are flush.

- The inner annular shoulder 34 to which the hydrophobic membrane 24 is secured within the lid 31 is close to the top wall 59 of the lid 31. The hydrophobic membrane 24 can deform under positive pressure until it abuts against the top wall 59 of the lid 31. The lid 31 therefore protects the hydrophobic membrane 24 not
15 only against outside blows but also from high positive pressure.

20

Figure 10 shows a fourth embodiment of an end-cap assembly according to the invention. The end-cap assembly comprises a convex, conical end-wall 60 connected to a tubular peripheral wall 61 by which the end-cap assembly can be secured to the housing of a filter. The conical end-wall 60 delimits the first
25 chamber 21 of a degassing device 205, which has therefore a decreasing section in the direction of flow. The conical end-wall 60 comprises an aperture at the tip thereof that forms a passageway 28 between the first chamber 21 and a second chamber 22. The second chamber 22 is delimited by a cylindrical wall 62 connected to the conical wall 60, and by the corresponding portion of the conical
30 wall 60, which forms the bottom of the second chamber 22. The central axis of the cylindrical wall 62 is parallel to and offset with respect to the central axis 27 of the conical end-wall 60 (and of the degassing device) and the passageway 28 opens in the second chamber 22 adjacent to the cylindrical wall 62. A circular hydrophobic membrane 24 is secured to the upper rim of the cylindrical wall 62 so

as to close the second chamber 22. A capsule like lid 63 having a series of vents 64 is engaged on the cylindrical wall 62 over the hydrophobic membrane 24 so as to protect the membrane 24 from outside and to support it and limit its deformation when it is subjected to a positive pressure from inside the filter. An outlet nozzle 65
5 forming the outlet port 25 of the degassing device 205 is connected to the cylindrical wall 62 opposite to the passageway 26.

The operation of the degassing device of figure 10, when connected to an extracorporeal blood circuit, is as follows. Since the cross-section of the second
10 chamber 22 at the level of the passageway 28 is substantially larger than the cross-section of the passageway 28 itself, the blood flow substantially decreases when blood enters the second chamber 22. This helps the bubbles and micro-bubbles that may be present in blood to move upwards by gravity towards the hydrophobic membrane 24. Also, because blood is directed towards the
15 hydrophobic membrane 24 at the periphery of the second chamber 22, the flow of blood has a component that is tangential to the hydrophobic membrane 24. The membrane is therefore permanently swept and the creation of a static layer of blood foam on the inner surface of the membrane 24 is prevented. Instead, the bubbles and micro-bubbles are kept in a permanent motion at the vicinity of the
20 membrane 24, through which they pass shortly after entering the second chamber 22.

Figure 11 shows a fifth embodiment of the end-cap assembly according to the invention. In this embodiment, the end-cap consists of a cylindrical peripheral wall
25 71 that engages the end of the housing 2 of a filter 1.

The cylindrical peripheral wall 71 forms the lower part of a cylindrical wall 72 that delimits the first chamber 21 of a degassing device 206. The first chamber 21 has a constant circular cross-section and its diameter is the same as the inner
30 diameter of the end of the housing 2. The first chamber 21, which is centered on the longitudinal axis 27 of the degassing device 206, opens within a second chamber 22. The second chamber 22 is delimited by a cylindrical wall 73 concentric to the cylindrical wall 72 of the first chamber 21, and a bottom wall 74 that is beveled with respect to the longitudinal axis 27 of the degassing device

206. The passageway 28 between the two chambers 21, 22 has the same cross-section as the end of the housing 2 of the filter 1 and a liquid flown into the first chamber of the filter 1 passes therefore unimpeded from the hollow fibers 4 into the second chamber 22. The cross-section of the second chamber 22 at the level of the passageway 28 is larger than the cross-section of the passageway 28 and the second chamber 22 therefore forms an overflow for the first chamber 21. The upper part of the wall 73 that delimits the second chamber 22 is curved towards the longitudinal axis 27 of the degassing device 206 and defines an upper part of the second chamber 22 having a decreasing cross-section. The end of the wall 73 forks into two perpendicular circular rims 75, 76. A first rim 75 extends in a plane perpendicular to the longitudinal axis 27 so as to form an annular shoulder defining an opening 23 of the second chamber 22. This opening 23 is closed by a hydrophobic membrane 24 secured at its periphery to the annular shoulder. A second rim 76 extends parallelly to the longitudinal axis 27. A capsule like lid 77 having a series of vents 78 is engaged onto the second rim 76 so as to protect the membrane 24 from outside and to support it and limit its deformation when it is subjected to a positive pressure from inside the filter. The degassing device 206 comprises an outlet port 25 connected to the second chamber 22.
- The various embodiments of the invention described above are only to exemplify the invention. The scope of the invention is therefore not limited to any of them.

Claims

1. A degassing device (201; 202; 203; 204; 205; 206) comprising:
 - a first chamber (21) having an inlet for a liquid; and
 - a second chamber (22) having an opening (23) closed by a hydrophobic membrane (24) and an outlet (25) for discharging the liquid,
- 5 wherein the first chamber (21) has a downstream portion that partially extends within the second chamber (22) and communicates therewith by a passageway (28), and the second chamber (22) has a downstream portion that extends below the passageway (28) and asymmetrically surrounds the downstream portion of the first chamber (21).
- 10
2. A degassing device (201; 202; 203; 204; 205; 206) according to claim 1, wherein the downstream portion of the second chamber (22) has a lateral wall (29; 62) that surrounds a longitudinal axis (27) of the degassing device and a bottom wall (30; 60) that is inclined with respect to a longitudinal axis (27) of the
- 15 degassing device.
3. A degassing device (201; 202; 203; 204; 206) according to claim 2, wherein the downstream portion of the first chamber (21) has a lateral wall (26) that is concentric to the lateral wall (29) of the second chamber (22).
- 20
4. A degassing device (201; 202; 203; 204; 206) according to claims 3, wherein the lateral wall (26) of the downstream portion of the first chamber (21) and the lateral wall (29) of the downstream portion of the second chamber (22) are substantially cylindrical.
- 25
5. A degassing device (201; 202; 203; 204; 206) according to one of the claims 1 to 4, wherein the downstream portion of the first chamber (21) has a cross-section that is substantially the same as the cross-section of the passageway (28) between the first and the second chamber (22).
- 30
6. A degassing device (205) according to one of the claims 1 and 2, wherein the downstream portion of the first chamber (21) is substantially conical and the

22

passageway (28) between the first and the second chamber (22) opens at the tip of the cone.

7. A degassing device (205) according to claim 6, wherein the passageway (28) between the first and the second chamber (22) opens in the second chamber (22) close to a wall (62) delimiting an upstream portion of the second chamber (22).

8. A degassing device (201; 202; 205) according to one of the claims 1 to 7, wherein the first chamber (21) comprises an upstream portion having a decreasing cross section.

9. A degassing device (203; 204) according to one of the claims 1 to 7, wherein the first chamber (21) comprises an upstream portion having an increasing cross section.

10. A degassing device (201; 202; 203; 204; 206) according to one of the claims 1 to 9, wherein the second chamber (22) comprises an upstream portion extending above the passageway (28) that has a decreasing cross-section, with a larger cross-section that is substantially level with the passageway (28) and a smaller cross-section that is substantially level with the hydrophobic membrane (24).

11. A degassing device (201; 202; 203; 204) according to claim 10, wherein the upstream portion of the second chamber (22) is substantially frusto-conical.

12. A degassing device (201; 202; 203; 204; 205; 206) according to one of the claims 1 to 11, wherein the outlet port (25) opens in the downstream portion of the second chamber (22) at a location furthest to the passageway (28).

13. A degassing device (201; 202; 203; 204; 205; 206) according to one of the claims 1 to 12, wherein the ratio of the diameter of the passageway (28) to the diameter of the second chamber (22) at the level of the passageway (28) is comprised between about 0,2 and about 0,5.

14. A degassing device (201; 202; 203; 204; 205; 206) according to one of the claims 1 to 13, wherein the first chamber (21) of the degassing device has a downstream portion having a cross-section selected with respect to a maximal flow rate of a liquid in a circuit connected to the degassing device so that the velocity of the liquid in the downstream portion of the first chamber (21) is less than a predetermined velocity.
15. A degassing device (201; 202; 203; 204; 205; 206) according to claim 14, wherein the cross-section of the downstream portion of the first chamber (21) is selected with respect to a maximal flow rate of a liquid of about 500ml/min in a circuit connected to the degassing device so that the velocity of the liquid in the downstream portion of the first chamber (21) is less than about 3m/min.
16. A degassing device (201; 202; 203; 204; 205; 206) according to one of the claims 1 to 15, wherein the cross-section of the second chamber (22) of the degassing device at the level of the passageway (28) is selected so that the ratio of the velocity of a liquid within a downstream portion of the first chamber (21) to the velocity of the liquid within the second chamber (22) at the level of the passageway (28) is more than a determined value.
17. A degassing device (201; 202; 203; 204; 205; 206) according to claim 16, wherein the cross-section of the second chamber (22) of the degassing device at the level of the passageway (28) is selected so that the ratio of the velocity of the liquid within the downstream portion of the first chamber (21) to the velocity of the liquid within the second chamber (22) at the level of the passageway (28) is at least about 2.
18. A degassing device (201; 202; 203; 204; 205; 206) according to one of the claims 1 to 17, wherein the downstream portion of the second chamber (22) forms an overflow for a fluid flowing from the first chamber (21) into the second chamber (22).
19. A degassing device (201; 202; 203; 204; 205; 206) according to one of the claims 1 to 18, wherein the first chamber (21), the second chamber (22) and the

24

passageway (28) therebetween are arranged with respect to each other so that a flow pattern of a liquid flowing from the first chamber (21), through the second chamber (22) and to the outlet port (25) comprises a component that is tangential to the membrane.

5

20. A degassing device (201; 202; 203; 204; 205; 206) according to claim 19, wherein the flow pattern of a liquid flowing from the first chamber (21), through the second chamber (22) and to the outlet port (25) comprises an umbrella like component.

10

21. A degassing device (201; 202; 203; 204; 205; 206) according to one of the claims 1 to 20, wherein the first chamber (21), the second chamber (22) and the passageway (28) therebetween are arranged with respect to each other so that a flow of liquid flowing from the first chamber (21), through the second chamber (22) and to the outlet port (25) keeps gas bubbles in motion along an inner surface of the hydrophobic membrane (24).

15

22. A degassing device (201) according to one of the claims 1 to 21, further comprising an inlet port (38, 39, 40) for the infusion of liquid.

20

23. A degassing device (201) according to one of the claims 1 to 22, further comprising a pressure measurement port (38, 39, 40) for connection to a pressure sensor.

25

24. A degassing device (201; 202; 203; 204; 205; 206) according to any of the claims 1 to 24, further comprising a protective member (36, 44, 59, 63, 77) for protecting the hydrophobic membrane (24) against external blows and for limiting the deformation of the hydrophobic membrane (24) when the pressure of the liquid within the degassing device exceeds a limit.

30

25. A degassing device (201; 202; 203; 204; 205; 206) according to one of the claims 1 to 24, wherein the hydrophobic membrane (24) is arranged in a plane substantially perpendicular to a longitudinal axis (27) of the degassing device.

25

26. End-cap assembly for a filtration device (1) including a filtration membrane (4) arranged in an elongated housing (2), the end-cap assembly comprising:

- an end-cap (5; 50) having:

- an end wall (15; 51) having a central axis,

- a peripheral wall (16; 52; 61; 71) surrounding the end wall (15; 51), for connection to an end of the housing (2), and

- a degassing device (201; 202; 203; 204; 205; 206) according to one of the claims 1 to 25 connected to the end-cap (5, 50) so that the first chamber (21) of the degassing chamber is in fluid communication with an interior of the en-cap.

10

27. End-cap assembly according to claim 26, wherein the degassing device (201; 202; 205; 206) has a longitudinal axis (27) that coincides with the central axis of the end wall (15; 60) of the end-cap (5) and the first chamber (21) has a wall (26; 60; 72) directly connected to the end wall (15; 60) of the end-cap (5).

15

28. End-cap assembly according to claim 27, wherein the end wall (15) of the end-cap (5) is substantially annular and the wall of the first chamber (21) has circular cross section decreasing from a first end of larger section, by which the first chamber (21) is connected to the end wall (15) of the end cap (5), to a second end of smaller cross section forming the passageway (28) between the first chamber (21) and the second chamber (22).

29. End-cap assembly according to claim 26, wherein the degassing device (203) has a longitudinal axis (27) that is substantially parallel to and spaced apart from the central axis (3) of the end wall (51) of the end-cap (50), and the end cap assembly further comprises a lateral nozzle (53) for connecting an interior of the end-cap (50) to an inlet (54) of the first chamber (21) of the degassing device (203).

30. End-cap assembly according to claim 29, wherein the first chamber (21) has a wall having circular cross section increasing from a first end of smaller section, which forms the inlet (54) of the first chamber (21), to a second end of larger cross section, which forms the passageway (28) between the first and the second chamber (22).

31. Filtration device (1) comprising an end-cap assembly according to one of the claims 26 to 30.
- 5 32. Filtration device (1) according to claim 31, for the extracorporeal treatment of blood.

1/6




FIG. 1

2/6




FIG. 2




FIG. 3

3/6




FIG. 4




FIG. 5




FIG. 6




FIG. 7

5/6




FIG. 8






FIG. 9

6/6



INTERNATIONAL SEARCH REPORT

Internal application No
PCT/EP2004/012372

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 A61M1/36

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 A61M

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 4 231 871 A (LIPPS ET AL) 4 November 1980 (1980-11-04) column 7, line 17 - line 27; figure 10	1-32
Y	EP 0 292 445 A (SORIN BIOMEDICA S.P.A) 23 November 1988 (1988-11-23) claims; figure	1-32
A	WO 00/25843 A (LIFESTREAM INTERNATIONAL, INC) 11 May 2000 (2000-05-11) page 16, line 19 - page 17, line 21; figures 2,4,12	1-32
A	US 4 344 777 A (SIPOSS ET AL) 17 August 1982 (1982-08-17) abstract; figures 7,8	1,26,31
	----- -/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

° Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- * & * document member of the same patent family

Date of the actual completion of the international search

4 April 2005

Date of mailing of the international search report

11/04/2005

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Villeneuve, J-M

INTERNATIONAL SEARCH REPORT

Intern: ,pplication No
PCT/EP2004/012372

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 4 293 413 A (SCHNELL ET AL) 6 October 1981 (1981-10-06) abstract; figure 3 -----	26, 31
A	US 5 468 388 A (GODDARD ET AL) 21 November 1995 (1995-11-21) the whole document -----	1, 24
A	EP 0 245 782 A (DIDECO S.P.A) 19 November 1987 (1987-11-19) figures 1,2 -----	
A	US 4 806 135 A (SIPOSS ET AL) 21 February 1989 (1989-02-21) figures -----	

INTERNATIONAL SEARCH REPORT

Intern: Application No
PCT/EP2004/012372

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 4231871	A	04-11-1980	US 4211597 A 08-07-1980
		AT 379083 B 11-11-1985	
		AT 422078 A 15-04-1985	
		AU 520681 B2 18-02-1982	
		AU 3656178 A 06-12-1979	
		BE 868005 A1 11-12-1978	
		BR 7803726 A 20-03-1979	
		CA 1116096 A1 12-01-1982	
		CH 627369 A5 15-01-1982	
		DE 2824898 A1 21-12-1978	
		DK 258878 A 11-12-1978	
		FR 2393585 A1 05-01-1979	
		GB 1602060 A 04-11-1981	
		IT 1105134 B 28-10-1985	
		JP 54006398 A 18-01-1979	
		MX 146448 A 28-06-1982	
		NL 7806277 A ,B, 12-12-1978	
		NO 782025 A ,B, 12-12-1978	
		NZ 187456 A 08-10-1980	
		SE 441058 B 09-09-1985	
		SE 7806714 A 11-12-1978	
EP 0292445	A	23-11-1988	IT 1210742 B 20-09-1989
			DE 3860692 D1 31-10-1990
			EP 0292445 A1 23-11-1988
WO 0025843	A	11-05-2000	AU 1334600 A 22-05-2000
			WO 0025843 A1 11-05-2000
US 4344777	A	17-08-1982	US 4368118 A 11-01-1983
US 4293413	A	06-10-1981	AU 6709881 A 22-07-1981
			EP 0042424 A1 30-12-1981
			WO 8101793 A1 09-07-1981
US 5468388	A	21-11-1995	DE 4321927 A1 19-01-1995
			DE 9407371 U1 07-07-1994
EP 0245782	A	19-11-1987	IT 1189118 B 28-01-1988
			AU 582687 B2 06-04-1989
			AU 7274287 A 17-12-1987
			DE 3781199 D1 24-09-1992
			DE 3781199 T2 25-03-1993
			EP 0245782 A2 19-11-1987
			ES 2033722 T3 01-04-1993
			JP 1789744 C 29-09-1993
			JP 4072552 B 18-11-1992
			JP 63023673 A 30-01-1988
US 4806135	A	21-02-1989	NONE